



Piston seal Forseal FOA



DESCRIPTION


- Asymmetrical
- Single acting
- Tight fit on inner diameter
- V-spring as preload element
- Sealing material: PTFE

FUNCTION

- Sealing of pistons
- Use with one-sided pressure load

PRODUCT ADVANTAGES

- High chemical resistance
- Low friction even at low speed
- High wear resistance
- Suitable for dry running and deficient lubrication
- Wide temperature range
- No stick-slip effect
- High extrusion reliability
- Market-leading, proprietary design with the widest range of applications in all industries and for a variety of requirements
- Highest quality, durability and safety
- Best results in total cost of ownership



APPLICATIONS

- Hot water valves
- Pneumatic cylinders

APPLICATION LIMITS

- Permissible maximum values depending on the other operating conditions, see technical manual.

MEDIA RESISTANCE

- Please refer to resistance information in the chemical resistance guide at www.fst.com.

CONFORMITY AND CERTIFICATES

- Please consult the material data sheet valid for the respective material for current information on approvals and certificates, as this information depends on the compound and cannot be listed exhaustively here.

DESIGN GUIDELINE

- Please refer to the technical manual for design guidelines.

INSTALLATION GUIDELINE

- The prerequisite for perfect function of the seal is careful installation in accordance with the technical manual.

STORAGE ADVISE

- Storage temperature <25°C
- No direct heat sources
- No direct sunlight
- No condensation in the storage room
- No exposure to ozone or ionizing radiation
- Recommendations based on the revision of ISO 2230 dated 16.09.1992