

# Material 84 NBR 772

black

cross linking: sulfur

<b>revision index</b> 5	<b>revision date</b> 9/17/2020			ра	<b>ge</b> 1/2
Physical properties		nom	ninal range	typical values	
Density DIN EN ISO 1183-1, 23 ℃			1.27 ±0.02	1.27	g/cm³
Hardness DIN ISO 7619-1, Shore A, 23	°C		84 ±5	84	Shore
Rebound resilience DIN 53512				18	%
Modulus 100 %, DIN 53504, S2, 23 °C			> 4.5	7.8	MPa
Tensile strength DIN 53504, S2, 23 °C			> 11.5	14.8	MPa
Elongation at break DIN 53504, S2, 23 °C			> 240	300	%
Compression set DIN ISO 815, Slab I, 22 h, 100	°C, 25 %		< 50	37	%
Surface resistivity DIN IEC 60093, 50 %, 23 °C, 5	500 V			5,0 E +10	Ohm
Durchgangswiderstand 500 V, 23 °C, 50 %				3,5 E +09	Ohm
Temperature range		-20°C to 100°C			

#### **Declarations of conformity**

This overview is purely informative and does not constitute a declaration of conformity (DoC). Please refer to the actual declaration of conformity (DoC) including the conditions and its validity period.

	Country	Part	Remark	Expires
Info ROHS and ELV			EU 2000/53 (ELV) including EU 2011/65 and EU2015/863 (ROHS III)	see DoC

Freudenberg FST GmbH Technology&Innovation Material Compliance Telefon: -Fax: -Email: MaterialCompliance@fst.com



# Material 84 NBR 772

black

cross linking: sulfur

revision index 5

**revision date** 9/17/2020

page 2/2

No ASTM D2000 properties available

#### Temperature-range: - 20 °C to 100 °C

The given values are based on a limited number of tests on standard test pieces (2mm sheets) produced in the laboratory. The data from finished parts can deviate from above values depending on the manufactories process and the component geometry.

The data represents our present empirical values. It is incumbent on the person placing the order to examine whether it is suitable for its intended purpose, before using the product. All questions regarding the guarantee of this product are in line with our terms and conditions, inasmuch as statutory provisons do not plan for something else.

### Freudenberg

Freudenberg FST GmbH Technology&Innovation Material Compliance Telefon: -Fax: -Email: MaterialCompliance@fst.com